

Epoxy.com #15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)



HEALTH	1
FLAMMABILITY	1
PHYSICAL	0
PPE	X

Printed: 10/29/2015

Revision: 10/29/2015

1. Product and Company Identification

Product Code:	15-A		
Product Name:	Epoxy.com #15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)		
Trade Name:	Epoxy.com #15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)		
Manufacturer Information			
Company Name:	Epoxy Systems, Inc. 20774 W Pennsylvania Ave. Dunnellon, FL 34431		
Emergency Contact:	PERS	+1	(800)633-8253
Alternate Emergency Contact:	International	+1	(801)629-0667
Information:	Epoxy Systems, Inc.	+1	(352)489-1666
Email address:	www.epoxy.com		
Intended Use:	Industrial floor coatings.		

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Skin Corrosion/Irritation, Category 3	none	Warning	Causes mild skin irritation
Serious Eye Damage/Eye Irritation, Category 2B	none	Warning	Causes eye irritation
Skin Sensitization, Category 1B	Exclamation	Warning	May cause an allergic skin reaction

GHS Hazard Phrases

H316 - Causes mild skin irritation. H317 - May cause an allergic skin reaction.

H320 - Causes eye irritation.

H335 - May cause respiratory irritation.

GHS Precaution Phrases

P264 - Wash hands thoroughly after handling.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Response Phrases

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313 - If eye irritation persists, get medical advice/attention.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P310 - Immediately call a POISON CENTER or doctor/physician.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to local, state, and federal authority requirements.

Potential Health Effects (Acute and Chronic)

May cause eye irritation. May cause skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

#15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)

Printed: 10/29/2015

Revision: 10/29/2015

Inhalation

May cause respiratory irritation.

Skin Contact

May cause skin irritation.

Eye Contact

May cause eye irritation.

Ingestion

May be harmful if swallowed.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Oxirane, 2,2'-[[1-Methylethylidene)bis(4,1-phenyleneoxy methy	25085-99-8	75.0 -90.0 %
2. Oxirane, Mono.(.(C12-14-alkyloxy)methyl.). derivs.	68609-97-2	10.0 -25.0 %

4. First Aid Measures

Emergency and First Aid Procedures**In Case of Inhalation**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Call a physician immediately. Do not induce vomiting. For further assistance, contact your local Poison Control Center.

Signs and Symptoms Of Exposure

Moderate irritation effect.

5. Fire Fighting Measures

Flash Pt: > 200.00 F Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data available.

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Product is not considered a fire hazard. Closed containers may rupture (due to build up in pressure) when exposed to extreme heat.

#15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)

Printed: 10/29/2015

Revision: 10/29/2015

Hazardous Combustion Products

Hazardous decomposition products formed under fire conditions. Carbon dioxide, Carbon monoxide, Phenolics.

Suitable Extinguishing Media

Dry chemical or CO2. Foam.

Unsuitable Extinguishing Media

Do not use a direct water stream, which may spread fire.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and Storage

Hazard Label Information:

Avoid contact with skin and eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist.
Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Do not breathe vapor. Do not get in eyes, on skin or on clothing.

Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place.

Other Precautions

Wash thoroughly after handling.

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits
1. Oxirane, 2,2'-[[1-Methylethylidene)bis(4,1-phenyleneoxy methy	25085-99-8	No data.	No data.	No data.
2. Oxirane, Mono.((C12-14-alkyloxy)methyl). derivs.	68609-97-2	No data.	No data.	No data.

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene are recommended.

#15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)

Printed: 10/29/2015

Revision: 10/29/2015

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways. May be hazardous to the environment if released in large quantities.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid	
Melting Point:	NE	
Boiling Point:	NE	
Decomposition Temperature:	NE	
Autoignition Pt:	No data.	
Flash Pt:	> 200.00 F	Method Used: Pensky-Marten Closed Cup
Explosive Limits:	LEL: NE	UEL: NE
Specific Gravity (Water = 1):	~ 1.139	
Density:	~ 9.5 LB/GL	
Vapor Pressure (vs. Air or mm Hg):	NE	
Vapor Density (vs. Air = 1):	NE	
Evaporation Rate:	NE	
Solubility in Water:	~	
Solubility Notes	Practically insoluble.	
Percent Volatile:	0.0 % by volume.	
VOC / Volume:	NP	
HAP / Volume:	NP	
Saturated Vapor Concentration:	NE	

Appearance and Odor

Odor: Epoxy odor.

Appearance: Straw;straw-colored.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Reactivity

Avoid: acids, alkalis, oxidizing agents.

Conditions To Avoid - Instability

Extreme temperatures.

Incompatibility - Materials To Avoid

Avoid strong acids, bases, and oxidizing agents.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, Phenolics.

#15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)

Printed: 10/29/2015
Revision: 10/29/2015

Possibility of Hazardous Polymerization: Will occur [] Will not occur [X]

Polymerization:**Conditions To Avoid - Hazardous Reactions**

Will not undergo hazardous polymerization in normal storage conditions.

11. Toxicological Information**Toxicological Information**

May cause sensitization by skin contact.

Chronic Toxicological Effects

Skin sensitization.

Irritation or Corrosion

Skin Irritation. Irritating to eyes.

Symptoms related to Toxicological Characteristics

May cause redness, rash on skin.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Oxirane, 2,2'-[[1-Methylethylidene]bis(4,1-phenyleneoxy methy	25085-99-8	n.a.	n.a.	n.a.	n.a.
2. Oxirane, Mono.-(.C12-14-alkyloxy)methyl.). derivs.	68609-97-2	n.a.	n.a.	n.a.	n.a.

12. Ecological Information**General Ecological Information**

Avoid release to the environment. May be hazardous to the environment if released in large quantities.

Results of PBT and vPvB assessment

No data available.

Persistence and Degradability

Not readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

not reported, unknown.

13. Disposal Considerations**Waste Disposal Method**

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information**LAND TRANSPORT (US DOT)****DOT Proper Shipping Name**

Synthetic Resin Liquid. Not Regulated.

Precautionary Label

Avoid skin and eye contact. May cause eye and skin irritation. May cause skin sensitization. Wear protective equipment and clothing. Always read MSDS/SDS before use.

AIR TRANSPORT (ICAO/IATA)**ICAO/IATA Shipping Name**

Synthetic Resin Liquid. Not Regulated.

MARINE TRANSPORT (IMDG/IMO)**IMDG/IMO Shipping Name**

Synthetic Resin Liquid. Not Regulated.

#15 Clear Chemical Resistant Epoxy Coating/Binder (Top Coat)

Printed: 10/29/2015

Revision: 10/29/2015

Marine Pollutant: No**15. Regulatory Information****US EPA SARA Title III**

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Oxirane, 2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxy methy	25085-99-8	No	No	No	No
2. Oxirane, Mono.(.(C12-14-alkyloxy)methyl). derivs.	68609-97-2	No	No	No	No

Regulatory Information

SARA Section 311/312: Acute Health Hazard.

16. Other Information

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however Epoxy Systems Inc. makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.

Revision Date: 10/29/2015