


24 / 28 Epoxy Binder Fast Cure Hardener

Part B



HEALTH	3
FLAMMABILITY	1
PHYSICAL	0
PPE	X



Printed: 10/12/2015
Revision: 10/12/2015

1. Product and Company Identification

Product Code:	24 FCB	
Product Name:	24 / 28 Epoxy Binder Fast Cure Hardener	Part B
Trade Name:	24/ 28 Epoxy Binder Fast Cure Hardener	Part B
Manufacturer Information		
Company Name:	Epoxy Systems, Inc. 20774 W Pennsylvania Ave. Dunnellon, FL 34431	
Phone Number:	+1 (352) 489-1666	
Emergency Contact:	PERS (USA)	(800) 633-8253
Alternate Emergency Contact:	PERS (International)	+1 (801) 629 0667
Intended Use:	Industrial floor coatings.	

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Skin Sensitization, Category 1A	Exclamation point	Warning	May cause an allergic skin reaction
Skin Corrosion/Irritation, Category 1B	Corrosive	Danger	Causes severe skin burns and eye damage
Serious Eye Damage/Eye Irritation, Category 1	Corrosive	Danger	Causes serious eye damage
Acute Toxicity: Oral, Category 4	Exclamation point	Warning	Harmful if swallowed
Aquatic Toxicity (Acute), Category 3	none		Harmful to aquatic life
Aquatic Toxicity (Chronic), Category 3	none		Harmful to aquatic life with long lasting effects

GHS Hazard Phrases

- H317 - May cause an allergic skin reaction.
- H314 - Causes severe skin burns and eye damage.
- H318 - Causes serious eye damage.
- H302+332 - Harmfull if swallowed or if inhaled.
- H402 - Harmful to aquatic life.
- H412 - Harmful to aquatic life with long lasting effects.

GHS Precaution Phrases

- P262 - Do not get in eyes, on skin, or on clothing.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P362+364 - Take off contaminated clothing and wash it before reuse.
- P264 - Wash hands thoroughly after handling.
- P273 - Avoid release to the environment.

GHS Response Phrases

- P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P332+313 - If skin irritation occurs, get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.
- P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P315 - Get immediate medical advice/attention.

SAFETY DATA SHEET
24 / 28 Epoxy Binder Fast Cure Hardener

Page: 2
Printed: 10/12/2015
Revision: 10/12/2015

Part B

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P310 - Immediately call a POISON CENTER or doctor/physician.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 - Get medical attention/advice if you feel unwell.

P391 - Collect spillage.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to local, state, and federal authority requirements.

P405 - Store locked up.

Potential Health Effects (Acute and Chronic)

Corrosive! Damages skin and eyes.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Inhalation

May cause respiratory irritation.

Skin Contact

Causes severe skin irritation. Causes skin burns.

Eye Contact

Corrosive/irritation to eyes. Causes eye burns.

Ingestion

Harmful if swallowed.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Isophoronediamine	2855-13-2	50 - 70 %
2. 1,5-Pentanediamine, 2-methyl-	15520-10-2	15 - 30 %
3. Benzenemethanol	100-51-6	5.0 - 15 %
4. Bisphenol-a based epoxy resin	25068-38-6	<10 %
5. Salicylic acid	69-72-7	<10 %

4. First Aid Measures

Emergency and First Aid Procedures

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention immediately.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately.

Part B

Signs and Symptoms Of Exposure

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

5. Fire Fighting Measures

Flash Pt: > 200.00 F Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data available.

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Combustible material: may burn but does not ignite readily.

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Fire may produce irritating, corrosive and/or toxic gases.

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use a direct water stream, which may spread fire.

6. Accidental Release Measures**Steps To Be Taken In Case Material Is Released Or Spilled**

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and Storage**Hazard Label Information:**

Avoid contact with eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Wear all personal protection required in section 8.

Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible material.

Other Precautions

Wash thoroughly after handling.

Part B

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits
1. Isophoronediamine	2855-13-2	No data.	No data.	No data.
2. 1,5-Pentanediamine, 2-methyl-	15520-10-2	No data.	No data.	No data.
3. Benzenemethanol	100-51-6	No data.	No data.	No data.
4. Bisphenol-a based epoxy resin	25068-38-6	No data.	No data.	No data.
5. Salicylic acid	69-72-7	No data.	No data.	No data.

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene are recommended.

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Melting Point:	NE
Boiling Point:	NE
Decomposition Temperature:	NE
Autoignition Pt:	No data.
Flash Pt:	> 200.00 F Method Used: Pensky-Marten Closed Cup
Explosive Limits:	LEL: NE UEL: NE
Specific Gravity (Water = 1):	~ .942
Density:	~ 7.86 LB/GL
Vapor Pressure (vs. Air or mm Hg):	NE
Vapor Density (vs. Air = 1):	NE
Evaporation Rate:	NE

24 / 28 Epoxy Binder Fast Cure Hardener

Printed: 10/12/2015

Revision: 10/12/2015

Part B

Solubility in Water: No data.**Solubility Notes**

Partial solubility.

Percent Volatile: N.A.**VOC / Volume:** NP**HAP / Volume:** NP**Saturated Vapor Concentration:** NE**Appearance and Odor**

Odor: amine-like.

Appearance: Liquid. amber.

10. Stability and Reactivity**Stability:** Unstable [] Stable [X]**Reactivity**

Avoid: acids, Avoid uncontrolled contact with isocyanates. Avoid: Uncontrolled reactions with epoxies.

Conditions To Avoid - Instability

Extreme temperatures.

Incompatibility - Materials To Avoid

Avoid strong acids, bases, and oxidizing agents.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide.

Possibility of Hazardous Will occur [] Will not occur [X]**Polymerization:****Conditions To Avoid - Hazardous Reactions**

Will not undergo hazardous polymerization in normal storage conditions.

11. Toxicological Information**Toxicological Information**

May cause sensitization by skin contact.

Chronic Toxicological Effects

Skin sensitization.

Irritation or Corrosion

Corrosive! Damages skin and eyes.

Symptoms related to Toxicological Characteristics

May cause sensitization by skin contact. May cause skin irritation or burns.

Can cause eye irritation or burns.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Isophoronediamine	2855-13-2	n.a.	n.a.	n.a.	n.a.
2. 1,5-Pentanediamine, 2-methyl-	15520-10-2	n.a.	n.a.	n.a.	n.a.
3. Benzenemethanol	100-51-6	n.a.	n.a.	n.a.	n.a.
4. Bisphenol-a based epoxy resin	25068-38-6	n.a.	n.a.	n.a.	n.a.
5. Salicylic acid	69-72-7	n.a.	n.a.	n.a.	n.a.

12. Ecological Information**General Ecological Information**

Avoid release to the environment. Do not empty into drains. May be hazardous to the environment if released in large quantities.

24 / 28 Epoxy Binder Fast Cure Hardener

Printed: 10/12/2015

Revision: 10/12/2015

Part B

Results of PBT and vPvB assessment

No data available.

Persistence and Degradability

Not readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

not reported, unknown.

13. Disposal Considerations**Waste Disposal Method**

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information**LAND TRANSPORT (US DOT)**

DOT Proper Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Modified Cycloaliphatic Amines)
DOT Hazard Class:	8
DOT Hazard Label:	CORROSIVE
UN/NA Number:	UN1719
Packing Group:	III
Precautionary Label	Corrosive! Damages skin and eyes. May cause sensitization by skin contact. May be harmful if swallowed.

AIR TRANSPORT (ICAO/IATA)

ICAO/IATA Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Modified Cycloaliphatic Amines)
UN Number:	1719
Hazard Class:	8 - CORROSIVE
Packing Group:	III

MARINE TRANSPORT (IMDG/IMO)

IMDG/IMO Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S. (Modified Cycloaliphatic Amines)
UN Number: Hazard	1719
Class: Packing	8 - CORROSIVE
Group: IMDG EMS	III
Number: Marine	FA,SB
Pollutant:	No

15. Regulatory Information**US EPA SARA Title III**

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Isophoronediamine	2855-13-2	No	No	No	No
2. 1,5-Pentanediamine, 2-methyl-	15520-10-2	No	No	No	No
3. Benzenemethanol	100-51-6	No	No	No	No
4. Bisphenol-a based epoxy resin	25068-38-6	No	No	No	No
5. Salicylic acid	69-72-7	No	No	No	No

Regulatory Information

SARA Section 311/312: Acute, Chronic Health Hazard.

Part B**16. Other Information**

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however Epoxy Systems, Inc. makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.

Revision Date: 10/12/2015