


SAFETY DATA SHEET

301 Cold Cure Hardener - Part B



HEALTH	3
FLAMMABILITY	1
PHYSICAL	0
PPE	X



Printed: 10/22/2015
Revision: 10/22/2015

1. Product and Company Identification

Product Code: 301 Cold Cure-HARDENER

Product Name: 301 Cold Cure Hardener - Part B

Trade Name: 301 Cold Cure Hardener - Part B

Manufacturer Information

Company Name: Epoxy Systems, Inc
20774 W Pennsylvania Ave
Dunnellon, FL 34431

Phone Number: +1 (352) 489-1666

Emergency Contact: PERS (USA) (800) 633-8253

Alternate Emergency Contact: PERS (International) +1 (801) 629 0667

Intended Use: Industrial floor coatings.

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Skin Sensitization, Category 1B	Exclamation point	Warning	May cause an allergic skin reaction
Skin Corrosion/Irritation, Category 2	Exclamation point	Warning	Causes skin irritation
Serious Eye Damage/Eye Irritation, Category 1	Corrosive	Danger	Causes serious eye damage
Acute Toxicity: Oral, Category 4	Exclamation point	Warning	Harmful if swallowed
Aquatic Toxicity (Chronic), Category 2	Pollution		Toxic to aquatic life with long lasting effects
Aquatic Toxicity (Acute), Category 2	none		Toxic to aquatic life
Acute Toxicity: Inhalation, Category 4	Exclamation point	Warning	Harmful if inhaled

GHS Hazard Phrases

- H317 - May cause an allergic skin reaction.
- H315 - Causes skin irritation.
- H318 - Causes serious eye damage.
- H302 - Harmful if swallowed.
- H411 - Toxic to aquatic life with long lasting effects.
- H401 - Toxic to aquatic life.
- H332 - Harmful if inhaled.

GHS Precaution Phrases

- P202 - Do not handle until all safety precautions have been read and understood.
- P262 - Do not get in eyes, on skin, or on clothing.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P362+364 - Take off contaminated clothing and wash it before reuse.
- P273 - Avoid release to the environment.

GHS Response Phrases

- P302+352 - IF ON SKIN: Wash with plenty of soap and water. P333+313 - If skin irritation or rash occurs, seek medical advice/attention. P362 - Take off contaminated clothing.
- P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

SAFETY DATA SHEET

301 Cold Cure Hardener - Part B

Page: 2
Printed: 10/22/2015
Revision: 10/22/2015

and easy to do. Continue rinsing. P313 - Get medical advice/attention.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P310 - Immediately call a POISON CENTER or doctor/physician.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342 - If experiencing respiratory symptoms: P313 - Get medical advice/attention.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to local, state, and federal authority requirements.

P404 - Store in a closed container. P405 - Store locked up.

Potential Health Effects (Acute and Chronic)

May cause sensitization. May cause skin irritation or burns. May cause respiratory tract irritation. May cause allergic skin reaction. Can cause severe eye irritation.

Inhalation

Corrosive to respiratory tract. May cause respiratory sensitization.

Skin Contact

Contact with substance may cause severe burns to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eye Contact

Corrosive/irritation to eyes. Causes eye burns.

Ingestion

Harmful if swallowed. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Recommended Exposure Limits

Not established.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. 4-tert-Butylphenol	98-54-4	30 - 45 %
2. Phenol, 4-nonyl-, branched	84852-15-3	15 - 25 %
3. 1,3-Benzenedimethanamine	1477-55-0	10 - 20 %
4. Trimethylhexamethylenediamine	25620-58-0	10 - 20 %
5. Benzenemethanol	100-51-6	5.0 - 15 %

4. First Aid Measures

Emergency and First Aid Procedures

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention immediately.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Get medical attention immediately.

Signs and Symptoms Of Exposure

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: Can cause severe skin burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Inhalation: Vapors are irritating to the respiratory system, may cause throat pain and cough.

5. Fire Fighting Measures

Flash Pt: > 200.00 F Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data available.

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards

Combustible material: may burn but does not ignite readily.

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Fire may produce irritating, corrosive and/or toxic gases.

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use a direct water stream, which may spread fire.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL.

Absorb with sand or vermiculite and place in closed containers for disposal. Ventilate the area.

Protective Precautions, Protective Equipment and Emergency Procedures

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Where splashing is possible, full chemically resistant protective clothing, and boots are required.

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and Storage

Hazard Label Information:

Avoid contact with eyes. Do not get on skin and clothing. Avoid inhalation of vapor or mist. Store in a closed container.

Precautions To Be Taken in Handling

Provide adequate ventilation. Wear all personal protection required in section 8.

Precautions To Be Taken in Storing

Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible material.

Other Precautions

Wash thoroughly after handling.

8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TWA	Other Limits
1. 4-tert-Butylphenol	98-54-4	No data.	No data. No	No data.
2. Phenol, 4-nonyl-, branched	84852-15-3	No data.	data. CEIL:	No data.
3. 1,3-Benzenedimethanamine	1477-55-0	No data.	mg/m3	No data.
4. Trimethylhexamethylenediamine	25620-58-0	No data.	No data.	No data.
5. Benzenemethanol	100-51-6	No data.	No data.	No data.

Protective Equipment Summary - Hazard Label Information:

Neoprene gloves Safety glasses, or goggles. Impervious clothing. Chemical resistant boots

Respiratory Equipment (Specify Type)

Normally when good engineering controls are used, no respiratory protection is needed. However, if cured product is abraded by sanding or grinding use a NIOSH approved air-purifying respirator. Where risk assessment shows air-purifying respirators are appropriate use a dust mask type N95 (US) or type P1 (EN 143) respirator. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Eye Protection

Safety glasses, or goggles.

Protective Gloves

Nitrile rubber and Neoprene are recommended.

Other Protective Clothing

Where splashing is possible, full chemically resistant protective clothing, safety glasses or face shield and boots are required.

Engineering Controls (Ventilation etc.)

Good general ventilation should be sufficient to control airborne levels. Safety shower and eye bath.

Work/Hygienic/Maintenance Practices

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

Environmental Exposure Controls

Avoid runoff into storm sewers and ditches which lead to waterways.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Melting Point:	NE		
Boiling Point:	NE		
Decomposition Temperature:	NE		
Autoignition Pt:	No data.		
Flash Pt:	> 200.00 F Method Used: Pinsky-Marten Closed Cup		
Explosive Limits:	LEL: NE	UEL: NE	
Specific Gravity (Water = 1):	~ .988		
Density:	~ 8.24 LB/GL		
Vapor Pressure (vs. Air or mm Hg):	NE		
Vapor Density (vs. Air = 1):	NE		
Evaporation Rate:	NE		

SAFETY DATA SHEET
301 Cold Cure Hardener - Part B

Page: 5
Printed: 10/22/2015
Revision: 10/22/2015

Solubility in Water: NE

Solubility Notes

Slightly Soluble.

Percent Volatile: N.A.

VOC / Volume: NP

HAP / Volume: NP

Saturated Vapor Concentration: NE

Appearance and Odor

Odor: amine-like.

Appearance: Liquid. amber.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Reactivity

Avoid: acids, alkalis, oxidizing agents. Nitric Acids.

Conditions To Avoid - Instability

Extreme temperatures.

Incompatibility - Materials To Avoid

Avoid strong acids, bases, and oxidizing agents.

Hazardous Decomposition Or Byproducts

Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, and phenolics. Nitric Acids.

Nitrogen oxides, ammonia.

Possibility of Hazardous Will occur [] Will not occur [X]

Polymerization:

Conditions To Avoid - Hazardous Reactions

Will not undergo hazardous polymerization in normal storage conditions.

11. Toxicological Information

Toxicological Information

May be harmful if swallowed. May cause sensitization by skin contact. Vapors may be harmful to the respiratory tract.

Chronic Toxicological Effects

May cause skin sensitization.

Irritation or Corrosion

Corrosive! Damages skin and eyes. May cause respiratory irritation.

Symptoms related to Toxicological Characteristics

Skin: Contact with substance may cause severe burns to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Permanent eye damage including blindness could result.

Inhalation: Inhalation of vapors/fumes causes respiratory irritation with throat discomfort, coughing or difficulty breathing.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. 4-tert-Butylphenol	98-54-4	n.a.	n.a.	n.a.	n.a.
2. Phenol, 4-nonyl-, branched	84852-15-3	n.a.	n.a.	n.a.	n.a.
3. 1,3-Benzenedimethanamine	1477-55-0	n.a.	n.a.	n.a.	n.a.

SAFETY DATA SHEET

301 Cold Cure Hardener - Part B

Page: 6
Printed: 10/22/2015
Revision: 10/22/2015

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
4. Trimethylhexamethylenediamine	25620-58-0	n.a.	n.a.	n.a.	n.a.
5. Benzenemethanol	100-51-6	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information

Avoid release to the environment. Do not empty into drains. May be hazardous to the environment if released in large quantities. Very toxic to aquatic life with long lasting effects.

Results of PBT and vPvB assessment

No data available.

Persistence and Degradability

Not readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

not reported, unknown.

13. Disposal Considerations

Waste Disposal Method

Incinerate or dispose of unused material, residues and containers in a licensed facility in accordance with all applicable local, state and federal regulations. Do not discharge substance/product into sewage system.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name

CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Cycloaliphatic Amines) MARINE POLLUTANT.

Marine Pollutant(s): Nonylphenol.

NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

DOT Hazard Class:

8

DOT Hazard Label:

CORROSIVE

UN/NA Number:

UN1719

Packing Group:

III

Precautionary Label

Corrosive! Damages skin and eyes. Avoid skin and eye contact. May cause eye and skin irritation. May cause skin sensitization. Wear protective equipment and clothing. Always read MSDS/SDS before use.

AIR TRANSPORT (ICAO/IATA)

ICAO/IATA Shipping Name

CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Cycloaliphatic Amines) MARINE POLLUTANT.

Marine Pollutant(s): Nonylphenol.

NOTE: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

SAFETY DATA SHEET

301 Cold Cure Hardener - Part B

Page: 7
Printed: 10/22/2015
Revision: 10/22/2015

UN Number: 1719
Hazard Class: 8 - CORROSIVE
Packing Group: III

MARINE TRANSPORT (IMDG/IMO)

IMDG/IMO Shipping Name CAUSTIC ALKALI LIQUID, N.O.S. (Contains Nonyl Phenol, Cycloaliphatic Amines) MARINE POLLUTANT.

Marine Pollutant(s): Nonylphenol.

UN Number: Hazard 1719
Class: Packing 8 - CORROSIVE
Group: IMDG EMS III
Number: Marine FA,SB
Pollutant: Yes

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. 4-tert-Butylphenol	98-54-4	No	No	No	No
2. Phenol, 4-nonyl-, branched	84852-15-3	No	No	No	No
3. 1,3-Benzenedimethanamine	1477-55-0	No	No	No	No
4. Trimethylhexamethylenediamine	25620-58-0	No	No	No	No
5. Benzenemethanol	100-51-6	No	No	No	No

Regulatory Information

SARA Section 311/312: Acute, Chronic Health Hazard.

16. Other Information

CA=CIRCA NA=NOT AVAILABLE NE=NOT ESTABLISHED NR=NOT REGULATED NP= NOT APPLICABLE PR=PROPRIETARY TS=TRADE SECRET ?=UNKNOWN.

Company Policy or Disclaimer

The information contained in this MSDS is taken from sources believed to be accurate as of the date hereof; however Epoxy Systems, Inc. makes no expressed or implied warranty in respect to the accuracy of the information or the suitability of the recommendations, and assumes no liabilities to any user thereof.

Revision Date: 10/22/2015